

06/14/00  
jc585 U.S. PTO

S&H Form: PTO/SB/05 (12/97)

# UTILITY PATENT APPLICATION TRANSMITTAL

Attorney Docket No. 1081.1091/JDH

First Named Inventor or Application Identifier:

Katsuya IRIE, et al.

Express Mail Label No.

(Only for new nonprovisional applications under 37 CFR 1.53(b))

jc585 U.S. PTO  
09/593424

06/14/00

## APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: **Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231**

1. ☒ Fee Transmittal Form
2. ☒ Specification, Claims & Abstract ..... [ Total Pages: 25 ]
3. ☒ Drawing(s) (35 USC 113) ..... [ Total Sheets: 10 ]
4. ☒ Oath or Declaration ..... [ Total Pages: 3 ]
  - a. ☒ Newly executed (original or copy)
  - b. ☐ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed)
    - i. ☐ **DELETION OF INVENTOR(S)**  
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation by Reference (usable if Box 4b is checked)  
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
  - a. ☐ Computer Readable Copy
  - b. ☐ Paper Copy (identical to computer copy)
  - c. ☐ Statement verifying identity of above copies

## ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) [ ] Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☒ Information Disclosure Statement (IDS)/PTO-1449[X] Copies of IDS Citations
12. ☒ Preliminary Amendment
13. ☐ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14. ☐ Small Entity Statement(s) [ ] Statement filed in prior application, status still proper and desired.
15. ☒ Certified Copy of Priority Document(s) (if foreign priority is claimed)
16. ☐ Other:

## 17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

[ ] Continuation [ ] Divisional [ ] Continuation-in-part (CIP) of prior application No:     /    

## 18. CORRESPONDENCE ADDRESS

STAAS & HALSEY LLP  
Attn: James D. Halsey, Jr.  
700 Eleventh Street, N.W., Suite 500  
Washington, DC 20001

Telephone: (202) 434-1500  
Facsimile: (202) 434-1501

# NEW APPLICATION FEE TRANSMITTAL

Attorney Docket No. 1081.1091/JDH

Application Number New

Filing Date June 13, 2000

AMOUNT ENCLOSED \$1,042.00

First Named Inventor Katsuya IRIE, et al.

## FEE CALCULATION (fees effective 12/29/99)

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS	10 - 20 =	0	X \$ 18.00 =	\$ 0.00
	INDEPENDENT CLAIMS	7 - 3 =	4	X \$ 78.00 =	312.00
	MULTIPLE DEPENDENT CLAIMS (any number; if applicable)			+ \$260.00 =	
				<b>BASIC FILING FEE</b>	690.00
				Total of above Calculations =	\$ 1002.00
	Surcharge for late filing fee, Statement or Power of Attorney (\$130.00)				+
	Reduction by 50% for filing by small entity (37 CFR 1.9, 1.27 & 1.28).				-
				<b>TOTAL FILING FEE =</b>	\$ 1002.00
	Surcharge for filing non-English language application (\$130.00; 37 CFR 1.52(d))				+
	Recordation of Assignment (\$40.00; 37 CFR 1.21(h)(1))				40.00
				<b>TOTAL FEES DUE =</b>	\$ 1042.00

## METHOD OF PAYMENT

- ☒ Check enclosed as payment.
- ☐ Charge "TOTAL FEES DUE" to the Deposit Account No., below.
- ☐ No payment is enclosed and no charges to the Deposit Account are authorized at this time.

## GENERAL AUTHORIZATION

- ☒ If the above-noted "AMOUNT ENCLOSED" is not correct, the Commissioner is hereby authorized to credit any overpayment or charge any additional fees necessary to:

Deposit Account No.


19-3935

Deposit Account Name

STAAS &amp; HALSEY LLP

- ☒ The Commissioner is also authorized to credit any overpayments or charge any additional fees required under 37 CFR 1.16 (filing fees) or 37 CFR 1.17 (processing fees) during the prosecution of this application, including any related application(s) claiming benefit hereof pursuant to 35 USC § 120 (e.g., continuations/divisionals/CIPs under 37 CFR 1.53(b) and/or continuations/divisionals/CPAs under 37 CFR 1.53(d)) to maintain pendency hereof or of any such related application.

## SUBMITTED BY: STAAS & HALSEY LLP

Typed Name	James D. Halsey, Jr.	Reg. No.	22,729
Signature		Date	June 13, 2000

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In re Application of:	)	
	)	
Katsuya IRIE, et al.	)	
	)	Group Art Unit: To Be Assigned
Serial No.: To Be Assigned	)	
	)	
Filed: June 13, 2000	)	Examiner: To Be Assigned
	)	
For: PLASMA DISPLAY PANEL WITH	)	
CONSTANT COLOR TEMPERATURE	)	
OR COLOR DEVIATION	)	

**PRELIMINARY AMENDMENT**

Assistant Commissioner of Patents and Trademarks  
Washington, D.C. 20231

Sir:

Before examination of the above-identified application, please amend the application as follows:

**IN THE CLAIMS:**

**Claim 4,** line 2, change "Claim 2 or Claim 3" to --claim 3--.

**Claim 5,** line 2, change "Claim 2 or Claim 3" to --claim 3--.

**Claim 6,** line 2, change "Claim 2 or Claim 3" to --claim 3--.

**REMARKS**

This Preliminary Amendment is submitted to improve the form of the claims as originally filed.

It is respectfully requested that this Preliminary Amendment be entered in the above-references application.

If any fees are required in connection with the filing of this Preliminary Amendment, please charge same to our Deposit Account No. 19-3935.

Respectfully submitted,

STAAS & HALSEY, LLP

By: 

James D. Halsey, Jr.  
Registration No.: 22,729

700 Eleventh Street, N.W.  
Washington, D.C. 20001  
(202) 434-1500

Date: June 13, 2000

004750-42425560

PLASMA DISPLAY PANEL WITH CONSTANT COLOR TEMPERATURE OR COLOR  
DEVIATION

BACKGROUND OF THE INVENTION

5

1. Field of the Invention

0959444-061470  
The present invention relates to a plasma display panel  
(hereafter PDP), and more particularly to a PDP which can keep  
color temperature or color deviation constant regardless the  
10 display load factor.

2. Description of the Related Art

PDP is a flat display panel which implements a 42 inch large  
screen. PDP has a gas discharge space where discharge gas is  
15 sealed between the front face side substrate and the rear face  
side substrate. By ultra-violet rays generated by the space  
charges, ions and electrons, which are generated by discharging  
in the gas discharge space, fluorescent substances formed inside  
are excited and the desired color display is implemented.

20 Generally fluorescent substances for three primary colors, red  
(R), green (G) and blue (B) are formed in each pixel, and the  
color display based on the combination of the three primary  
colors is executed by controlling the each emission intensity  
in each pixel.

25 In this case, if the grayscale of RGB is 256, for example,  
a black display is executed when all the grayscales of RGB are  
0, and the white display is executed when all the grayscales

of RGB are 256. When the grayscales of RGB are less than 256 but are all equal, the white display with low luminance (gray) is executed.

Fig. 1 is a curve of color temperature. The abscissa is the x chromaticity coordinate, and the ordinate is the y chromaticity coordinate. The curve with 0 deviation is a black body radiation curve where the color temperature changes along the curve. Along this black body radiation curve, a bluish white is generated if the color temperature is high, and yellowish white is generated if the color temperature is low. Also, at each color temperature, a greenish white is generated if deviation shifts to the positive direction and reddish white is generated if deviation shifts to the negative direction.

For the color temperature of white created by three primary colors, it is generally said that 9000 - 10000K is the optimum for Japanese. And it is said that 6000K is the optimum for Europeans and Americans. White for PDP is desirable to be set to the above optimum color temperature values.

Fig. 2 are drawings depicting the relationship between the display load factor, color temperature value and color temperature deviation of a general PDP. Fig. 2A shows the relationship between the display load factor and the color temperature value of white to be displayed for three types of PDPs, and Fig. 2B shows the relationship between the display load factor and the color temperature deviation of white to be displayed for the same three types of PDPs. The display load factor is a ratio of the display load which depends on luminance

and/or display area of a display image, where (1) when 256  
grayscales, which is the maximum grayscale, of white is  
displayed on the entire display screen, and the display load  
factor is 100%, (2) the display load factor decreases as the  
ratio of white to black in the display screen decreases, and  
(3) the display load factor decreases as the grayscale value  
of white decreases even if the ratio of the white to black is  
the same.

As Fig. 2A shows, in the case of a PDP made by company B,  
for example, the color temperature value when the display load  
factor is 30% is 10000K, where roughly an optimum white is  
displayed, but as the display load factor increases, the color  
temperature value of white decreases and white becomes yellowish.  
This tendency is the same for the PDPs made by company A and  
company C.

As Fig. 2B shows, in the case of company A and company C,  
the deviation of the color temperature is almost 0 when the  
display load factor is about 30%, but as the display load factor  
increases, the deviation changes to the positive side and white  
becomes greenish.

It is a serious problem where white turns a color in this  
manner depending on the display load factor.

#### SUMMARY OF THE INVENTION

It is accordingly an object of the present invention to  
provide a PDP where the chromaticity coordinates of white do

not fluctuate depending on the display load factor.

It is another object of the present invention to provide a PDP where the color temperature of white does not fluctuate depending on the display load factor.

5 It is still another object of the present invention to provide a PDP where the deviation of the chromaticity coordinate values of white on the black body radiation curve do not fluctuate even if the display load factor changes.

10 To achieve the above objects, one aspect of the present invention is characterized in that the PDP drive means makes correction so as to decrease the emission intensity of green or to increase the emission intensity of blue as the display load factor increases compared with the case when the display load factor is lower. Or, the PDP drive means makes correction  
15 so as to increase the emission intensity of green or to decrease the emission intensity of blue as the display load factor decreases compared with the case when the display load factor is higher. Such a correction is effective when the monochromatic emission luminance of the fluorescent substance  
20 has such a saturation characteristic that the decrease in green is greater than blue as the emission frequency increases. Therefore, when the saturation characteristic is the opposite in terms of the relationship between green and blue, the increase/decrease of the emission intensity in the above  
25 correction must be the opposite.

There are various ways to detect the display load factor. In a preferred embodiment, for example, the power consumption



of the panel is monitored, and if the power consumption increases, display is corrected such that the emission intensity of green is decreased or the emission intensity of blue is increased. If power consumption decreases, on the other hand, display is  
5 corrected such that the emission intensity of green is increased or the emission intensity of blue is increased.

In the case of another preferred embodiment, the drive frequency of the sustain discharge pulse is monitored and if the drive frequency decreases, display is corrected such that  
10 the emission intensity of green is decreased or the emission intensity of blue is increased. If the drive frequency increases, on the other hand, display is corrected such that the emission intensity of green is increased or the emission intensity of blue is decreased.

As the above mentioned correction method for increasing or decreasing the emission intensity, increasing or decreasing the signal intensity of green and blue to be supplied is preferable. Because of this, the signal intensity of green for white, for example, is corrected to be lower as the display load  
15 factor increases so that white, which is the same as when the display load factor is lower, is displayed.  
20

The above invention prevents the optimum chromaticity coordinate values from deviating by the fluctuation of the color temperature value or by the deviation of the color temperature  
25 of white to be displayed along with the fluctuation of the display load factor.

To achieve the above objects, another aspect of the present

invention is characterized in that the PDP drive means controls the drive frequency of the sustain discharge pulse so as to be limited in the range where the emission intensity of the fluorescent substances of the panel does not saturate. In this case, when the emission intensity of the fluorescent substances of RGB of the panel have different saturation characteristics as the drive frequency increases, the drive means does not use the drive frequency which reaches the saturation area. Therefore, influence by the emission intensity saturation characteristic of the fluorescent substances of RGB is eliminated, the color temperature value or the deviation of the color temperature of white to be displayed is kept roughly constant without depending on the display load factor, and deviation from the optimum chromaticity coordinate values is prevented.

To achieve the above objects, the present invention is a plasma display panel which displays colors by exciting a plurality of fluorescent substances using ultra-violet rays generated during discharge, wherein depending on a change of the display load factor, the plasma display panel drive unit corrects display by changing the emission intensity of a fluorescent substance of a predetermined color so that the ratio of the emission intensity of the above fluorescent substance of each color during white display is roughly the same when the above display load factor is low and high.

It is still another object of the present invention to provide a PDP where white does not turn color depending on the

display load factor by maintaining the chromaticity coordinate values during white display within  $\pm 0.005uv$  of the deviation area from the color temperature curve denoted by the black body radiation curve, regardless the display load which depends on the luminance of the display image or display area.

#### BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a drawing depicting the color temperature curve;

Fig. 2 are drawings depicting the relationship between the display load factor, color temperature value and color temperature deviation of a general PDP;

Fig. 3 is a drawing depicting the relationship between the display load factor, power consumption and drive frequency of a PDP;

Fig. 4 is a drawing depicting the relationship between the drive frequency  $f$  and the monochromatic emission luminance of the fluorescent substances of a PDP;

Fig. 5 is a table showing the display load factor, drive frequency and color temperature characteristics;

Fig. 6 is a drawing depicting a panel configuration of the PDP to which the present embodiment is applied;

Fig. 7 is a drawing depicting an example of the drive pulse waveform of the PDP shown in Fig. 6;

Fig. 8 is a drawing depicting a configuration example of the PDP and the drive unit according to the first embodiment;

Fig. 9 is a drawing depicting a configuration example of

the PDP and the drive unit according to the second embodiment;  
and

Fig. 10 is a drawing depicting a configuration example of  
the PDP and the drive unit according to the third embodiment.

5

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of the present invention will now be described  
with reference to the accompanying drawings. These embodiments,  
10 however, do not restrict the technical scope of the present  
invention.

Fig. 3 is a drawing depicting the relationship between the  
display load factor, power consumption and drive frequency of  
a PDP. As the display load factor increases, that is, as the  
15 display area increases and the display luminance of white  
increases, the required number of times of emissions during the  
sustain discharge increases and the power consumption of the  
panel increases. In a normal PDP, however, an increase in power  
consumption is not desirable and the drive circuit limits the  
20 drive frequency during the sustain discharge so that the power  
consumption is clamped to a predetermined value even if the  
display load factor increases. In other words, when the display  
load factor further increases after the predetermined display  
load factor is exceeded, as shown in Fig. 3, the drive circuit  
25 controls to decrease the drive frequency so that the power  
consumption is clamped to a predetermined value.

Fig. 4 is a drawing depicting the relationship between the

drive frequency  $f$  and the monochromatic emission luminance of the fluorescent substances of the PDP. The monochromatic emission luminance of a fluorescent substance which can be used for PDP is generally low in the area where the drive frequency is low, and the monochromatic emission luminance increases as the drive frequency increases and the number of times of emission increases. However, as Fig. 4 shows, the emission luminance of the fluorescent substance of each RGB color reaches the saturation area when the drive frequency is further increased. Also, in the saturation characteristics of the fluorescent substances of RGB, the emission luminance of the green fluorescent substance drops considerably and the emission luminance of the blue fluorescent substance does not drop very much. Such saturation characteristics are unique to fluorescent substances, and at the moment almost all available fluorescent substances have such saturation characteristics.

The drive method shown in Fig. 3 and the saturation characteristic of the fluorescent substance in Fig. 4 seem to be some of the reasons for the chromaticity coordinate values of white shown in Fig. 2 to fluctuate. Fig. 5 is a table showing the display load factor, drive frequency and color temperature characteristics according to the phenomena shown in Fig. 3 and Fig. 4. Case A is the case when the display load factor is small and case B is the case when the display load factor is large.

Comparing case A, where the display load factor is small, and case B, where the display load factor is large, the drive frequency is high in case A and low in case B, and power

consumption decreases in case A and increases in case B, as Fig. 3 shows. Also as Fig. 4 shows, the emission intensity of green is stronger and the emission intensity of blue is weaker in case B, where the display load factor is high, compared with case A, where the display load factor is low, due to the saturation characteristics of the fluorescent substances.

Therefore, when the relative composing ratio of each color in white is set to the optimum in the area where the display load factor is low, for example, correction is made such that the emission intensity of green is decreased in case B, where the display load factor is high, more so than case A, where the display load factor is low. Or, correction is made such that the emission intensity of blue is increased in case B, where the display load factor is high, more so than case A, where the display load factor is low. Or, green and blue are simultaneously corrected.

When the relative composing ratio of each color in white is set to an optimum in the area where the display load factor is high, on the other hand, correction is made such that the emission intensity of green is increased in case A, where the display load factor is small, more so than case B, where the display load factor is high. Or, correction is made such that the emission intensity of blue is decreased in case A, where the display load factor is low, more so than case B, where the display load factor is high. Or, green and blue are simultaneously corrected.

Fig. 6 is a drawing depicting a panel configuration of the

PDP to which the present invention is applied. The front face side substrate 1 is a transparent substrate and is comprised of a glass substrate 1, for example. On the front face side glass substrate 1, an X electrode and a Y electrode are alternately disposed as the sustain electrode 2, where the X electrode and the Y electrode form a display electrode pair. A protective layer 3 which consists of a dielectric layer and MgO is formed on the sustain electrode 2. The rear face side substrate 11 is comprised of a glass substrate, for example, where a plurality of address electrodes 12, a dielectric layer, which is not illustrated, fluorescent substances 13R, 13G and 13B for the three primary colors red (R), green (G) and blue (B), and ribs 14 are disposed in the orthogonal direction to the sustain electrode 2. A rib 14 is formed between the address electrodes 12. A discharge gas, which is not illustrated, is filled between the substrates.

Each pixel has fluorescent substances 13R, 13G and 13B for RGB respectively, and a desired color is displayed by the combination of the emission intensity of the three primary colors. When the emission intensity of the three primary colors are all at a maximum, for example, white, which has the maximum grayscales, is reproduced, and when the emission intensity of the three primary colors are all zero, black is reproduced.

Fig. 7 is a drawing depicting an example of the drive waveform pulse of the PDP shown in Fig. 6. Fig. 7 shows a drive waveform pulse in one sub-frame. Each one of the address electrodes A1, A2, . . . Am is connected to the address driver,

and the address pulses  $A(1), A(2), \dots A(n)$  are applied during the addressing period  $T_a$  according to the display data. The Y electrodes  $Y_1, Y_2, \dots Y_n$  are connected to the Y scan driver, and a selection pulse is applied from the Y scan driver during address scanning, and a sustain discharge pulse is applied from the Y common driver during emission (sustain period). The X electrodes are all connected to the X common driver from which a pulse is applied. These driver circuits are controlled by the control circuit and are controlled based on the synchronization signals and input signals, including data from the outside.

The grayscale of the plasma display panel is displayed by matching each bit of the display data to the sub-frame period and changing the length of the sustain discharge period in the sub-frame according to the weighting of the bit. For example, when  $2^j$  grayscale display is executed with  $j$  bits, one frame is divided into  $j$  number of sub-frames. The length of the sustain discharge period  $T_{sf}(j)$  of each sub-frame is in the ratio of  $1:2:4:8: \dots : 2^{j-1}$ . Here, the address period  $T_a$  and the reset period  $T_r$  are the same lengths for all the sub-frames.

One sub-frame period consists of the reset period  $T_r$ , address period  $T_a$ , and the sustain discharge period  $T_s$  ( $T_{sf}$ ). In the reset period  $T_r$ , all the Y electrodes are set to 0V, pulses are applied to all the address electrodes and X electrodes respectively, and after all the cells discharge, a self-erasing discharge for self neutralization and for ending the discharge is executed. Then, in the addressing period  $T_a$ , address



selection and discharge are executed for each line to turn the cells on/off according to the display data, and the priming charge is stored. Then pulses are applied alternately to the X electrodes and Y electrodes for the sustain discharge during the sustain discharge period  $T_s$ , and an image for one sub-frame is displayed. The luminance is determined by the number of times of pulses during the sustain discharge period.

In this way, the luminance of 0 to  $2^{j-1}$  grayscales can be displayed by turning on the sub-frames from 1 to  $j$  selectively.

Increasing the drive frequency of the sustain discharge pulse in the sustain discharge period  $T_s$  increases the general number of times of emissions, and increases the luminance. Increasing the drive frequency, however, tends to increase the power consumption of the panel.

Fig. 8 is a drawing depicting a configuration example of the PDP and the drive unit according to the first embodiment. The PDP and the drive unit 80 are connected, for example, by a flexible cable. In Fig. 8, the address electrodes A, X electrodes X, Y electrodes Y and the pixels C are shown in the PDP.

The drive unit 80 comprises address drivers 89A and 89B for driving the address electrodes A, a scan driver 86 for driving the Y electrodes during scanning, an X common driver 85 for commonly driving the X electrodes, and Y common driver 87 for commonly driving the Y electrodes. The image data DF for each frame from the outside includes RGB image data, and is stored in a frame memory 830 in a data processing circuit 83 via a signal

intensity adjustment part 91. Synchronization signals  $V_{sync}$  and  $H_{sync}$  from the outside are supplied to a scan controller 81 and a common driver controller 82 respectively.

The data processing circuit 83, the scan controller 81 for  
5 controlling panel driving and the common driver controller 82  
constitute the control circuit 90. The data processing circuit  
83 executes, for example, gamma conversion and conversion to  
the sub-field data  $D_{sf}$  based on binary processing for the  
supplied RGB image data for each frame, and stores the result  
10 to the frame memory 830. And, the sub-field data  $D_{sf}$  is supplied  
to the address drivers 89A and 89B according to the timing signal,  
which is not illustrated, from the scan controller 81.

The scan controller 81 supplies the timing signal to the  
scan driver 86 during the address period  $T_A$  according to the  
15 above mentioned synchronization signal to be supplied. The  
common driver 82 supplies predetermined timing signals to the  
X and Y common drivers 85 and 87 during the reset period  $T_R$  and  
the sustain discharge period  $T_S$ . The common driver 82 includes  
a function to control the drive frequency of the sustain  
20 discharge pulse during the sustain discharge period so that  
overall power consumption does not become higher than a  
predetermined value.

This power consumption can be detected, for example, by  
the current to be consumed by the power supply circuit 84. The  
25 power consumption according to the display load factor can also  
be detected by the X common driver which supplies a drive pulse  
with the drive frequency to the X electrodes during the sustain

discharge period. In this case, a power detection part 92, illustrated in Fig. 8, detects the power consumption of the X common driver 85.

In the first embodiment, when the power consumption PW1 increases, as shown in Fig. 5, the signal intensity adjustment unit 91 adjusts the intensity of the green image signal included in the image signal to be decreased according to the change of power PW1 in the sustain discharge period detected by the power detection part 92. Or, the signal intensity adjustment unit 91 adjusts the intensity of the blue image signal included in the image signal to be increased.

When the power consumption PW1 decreases, as shown in Fig. 5, the signal intensity adjustment unit 91 adjusts the intensity of the green image signal included in the image signal to be increased. Or, the signal intensity adjustment unit 91 adjusts the intensity of the blue image signal included in the image signal to be decreased.

After the intensity of the green and/or blue image signals are adjusted, the image signals are supplied to the data processing circuit 83. Therefore, the color temperature value and the deviation of white are maintained a roughly at a constant regardless the level of power consumption.

The intensity of green and blue image signals can also be adjusted within the data processing part 83. For example, the intensity of green and blue image signals can be adjusted for correction by increasing or decreasing the output value of the gamma table during gamma conversion. By using the signal

intensity adjustment unit 91, a conventional data processing circuit 83 can be used as is.

A green and blue grayscale correction, similar to above, may be executed based on overall power fluctuation detected in the power supply circuit 84.

Fig. 9 is a drawing depicting a configuration example of the PDP and the drive unit according to the second embodiment. The configuration of the drive unit 80 is almost the same as the first embodiment in Fig. 8. The difference is that the image data DF for each field from the outside is supplied to the signal intensity adjustment unit 91 as well as to the signal intensity detection unit 93. The signal intensity detection unit 93 monitors the intensity of RGB image data, for example, and detects the accumulation of the intensity value for one field. By this, the display load factor of a PDP can be indirectly detected.

The signal intensity information (data) detected by the signal intensity detection unit 93 is supplied to the signal intensity adjustment unit 91. When the detected signal intensity increases, the signal intensity adjustment unit 91 adjusts the intensity of the green image signal included in the image signal to be decreased, as mentioned above. Or, the signal intensity adjustment unit 91 adjusts the intensity of the blue image signal included in the image signal to be increased.

Or, when the detected signal intensity decreases, the signal intensity adjustment unit 91 adjusts the intensity of the green image signal included in the image signal to be

increased. Or, the signal intensity adjustment unit 91 adjusts the blue image signal included in the image signal to be decreased.

After the intensity of the green and/or blue image signals is adjusted, the image signals are supplied to the data processing circuit 83. Therefore, the color temperature value and the deviation of white are maintained roughly at a constant regardless the level of power consumption.

Fig. 10 is a drawing depicting a configuration example of the PDP and the drive unit according to the third embodiment. The configuration of the drive unit 80 is almost the same as the first embodiment in Fig. 8. The difference is that the drive frequency detection unit 94 for detecting the drive frequency of the sustain discharge pulse in the sustain discharge period is disposed and the drive frequency  $f$  detected by the drive frequency detection unit 94 is supplied to the signal intensity adjustment unit 91 and the data processing circuit 83. The drive frequency detection unit 94 detects, for example, the average of the number of sustain discharge pulses per unit time, and supplies the drive frequency data  $f$  to the signal intensity adjustment unit 91.

As Fig. 5 shows, the drive frequency  $f$  decreases as the display load factor increases. This is because the common driver controller 82 of the drive unit controls the drive frequency, as shown in Fig. 3, so that the power consumption does not become excessively high. Therefore, by monitoring the drive frequency  $f$ , the display load factor can be indirectly

monitored. Also, depending on the drive frequency  $f$ , the RGB fluorescent substances present the saturation characteristics as shown in Fig. 4.

So, when the drive frequency  $f$  decreases, the signal intensity adjustment unit 91 adjusts the intensity of the green image signal included in the image signal to be decreased. Or, the signal intensity adjustment unit 91 adjusts the intensity of the blue image signal included in the image signal to be increased.

Or, when the drive frequency  $f$  increases, the signal intensity adjustment unit 91 adjusts the intensity of the green image signal included in the image signal to be increased. Or, the signal intensity adjustment unit 91 adjusts the intensity of the blue image signal included in the image signal to be decreased.

The drive frequency  $f$  detected by the drive frequency detection unit 94 may be supplied to the data processing circuit 83. In this case, the luminance of green or blue can be adjusted by adjusting, for example, the output values of the gamma table in the gamma conversion processing in the data processing circuit 83.

The drive frequency  $f$  is determined by the common driver controller 82. Therefore, the determined information on the drive frequency  $f$  may be supplied to the signal intensity adjustment unit 91 and the data processing circuit 83 to make the above mentioned correction.

The fourth embodiment will now be described. In the fourth

embodiment, the drive frequency is monitored so that the drive frequency is limited within the frequency range fL shown in Fig. 4. For this, the drive frequency detection unit 94 shown in Fig. 10 monitors the drive frequency and the detected drive frequency f1 is fed back to the common driver controller 82. The common driver controller 82 controls the drive frequency so that the drive frequency f1 to be detected is maintained within the frequency range fL shown in Fig. 4.

By maintaining the drive frequency in the frequency range fL in this way, RGB fluorescent substances can be excited while avoiding the saturation characteristics. Therefore, the change of color temperature and change of deviation of white depending on the fluctuation of the display load factor can be prevented, and the relative ratio of colors to display an optimum white can be constantly maintained.

In the above embodiment, it is preferable to maintain the color temperature value of white to be displayed at  $\pm 200\text{K}$  or less of the set value, and the deviation at set value  $\pm 0.005\text{uv}$  or less.

In the above embodiment, if the chromaticity coordinate value of white to be displayed are set at the region of  $\pm 0.005\text{uv}$  from the color temperature curve denoted by the black body radiation curve, regardless the value of the display load factor, then a visually preferable white can be displayed because phenomena where white turns color depending on the display load factor does not occur.

In the above embodiment, if the chromaticity coordinate

value during a white display is moved such that the color temperature increases and the deviation is maintained as constant as the display load factor increases, then a white with a high color temperature can be displayed, that is, a visually preferable white can be displayed, when the image load factor is high.

In the above embodiment, if the saturation characteristics of the fluorescent substances shown in Fig. 4 differ, the intensity of each color must be adjusted accordingly.

In this way, according to the present invention, the color temperature value of white can be controlled to within a predetermined range depending on the display load factor. Or, the deviation of the color temperature curve of white can be controlled to within a predetermined range. Therefore, an optimum white or a white close thereto can always be displayed and high quality images can be displayed.

The protective scope of the present invention is not restricted by the above embodiments, but the claims and all the variations which come within the meaning of the claims are intended to be embraced therein.



What is Claimed Is:

1. A plasma display panel which displays colors by exciting a plurality of fluorescent substances of different colors using ultra-violet rays generated during discharge, comprising:

a drive unit which drives the panel with decreasing the drive frequency of the sustain discharge as the display load factor increases,

wherein said drive unit makes correction to change the emission intensity of a fluorescent substance of a predetermined color, so that the ratio of the emission intensity of said fluorescent substance of each color during white display is roughly the same when said display load factor is low and high, depending on a change of the display load factor.

2. A plasma display panel which displays colors by exciting a plurality of fluorescent substances of different colors using ultra-violet rays generated during discharge, comprising:

a drive unit which drives the panel with decreasing the drive frequency of the sustain discharge as the display load factor increases,

wherein when the display load factor increases, said drive unit makes correction so that the emission intensity of green is decreased or the emission intensity of blue is increased compared with the case when the display load factor is lower.

3. A plasma display panel which displays colors by exciting

a plurality of fluorescent substances of different colors using ultra-violet rays generated during discharge, comprising:

a drive unit which drives the panel with decreasing the drive frequency of the sustain discharge as the display load factor increases,

wherein when the display load factor decreases, said drive unit makes correction so that the emission intensity of green is increased, or the emission intensity of blue is decreased compared with the case when the display load factor is higher.

4. The plasma display panel according to Claim 2 or Claim 3, wherein said drive unit monitors the power consumption of the panel and corrects said emission intensity of green or blue on the condition that said display load factor increases when said power consumption changes to increase, and said display load factor decreases when said power consumption changes to decrease.

5. The plasma display panel according to Claim 2 or Claim 3, wherein said drive unit monitors the drive frequency of the sustain discharge of the panel, and corrects said emission intensity of green or blue on the condition that said display load factor increases when said drive frequency changes to decrease, and said display load factor decreases when said drive frequency changes to increase.

6. The plasma display panel according to Claim 2 or Claim 3,

wherein said drive unit monitors a luminance value and/or display area value of each color to be supplied per predetermined unit time, and corrects said emission intensity of green or blue on the condition that said display load factor increases when the accumulated total of said luminance value and/or display area value per predetermined unit time is higher, and said display load factor decreases when the accumulated total of said luminance value and/or display area value per predetermined unit time is lower.

7. A plasma display panel which display colors by exciting a plurality of fluorescent substances of different colors using ultra-violet rays generated during discharge, wherein a chromaticity coordinate value during white display is roughly constant regardless the display load which depends on the luminance and/or display area of the display image.

8. A plasma display panel which displays colors by exciting a plurality of fluorescent substances of different colors using ultra-violet rays generated during discharge, wherein a color temperature value during white display is roughly constant regardless the display load which depends on the luminance and/or display area of the display image.

9. A plasma display panel which displays colors by exciting a plurality of fluorescent substances of different colors using ultra-violet rays generated during discharge, wherein the

deviation from the color temperature curve denoted by the black body radiation curve during white display is roughly constant regardless the display load which depends on the luminance and/or display area of the display image.

5

10. A plasma display panel which displays colors by exciting a plurality of fluorescent substances of different colors using ultra-violet rays generated during discharge, wherein a chromaticity coordinate value during white display is within  $\pm 0.005uv$  of the deviation region from the color temperature curve denoted by the black body radiation curve regardless the display load which depends on the luminance and/or display area of the display image.

10

# ABSTRACT

The present invention is characterized in that the PDP drive means makes correction so as to decrease the emission intensity of green or to increase the emission intensity of blue as the display load factor increases compared with the case when the display load factor is lower. Or, the PDP drive means makes correction so as to increase the emission intensity of green or to decrease the emission intensity of blue as the display load factor decreases compared with the case when the display load factor is higher. Such a correction is effective when the monochromatic emission luminance of the fluorescent substance has such a saturation characteristic that the decrease in green is greater than blue as the emission frequency increases. Therefore, when the saturation characteristic is the opposite in terms of the relationship between green and blue, the increase/decrease of the emission intensity in the above correction must be the opposite.

FIG. 1

Color Temperature




FIG. 2A




FIG. 2B




FIG. 3






FIG. 4




FIG. 5  
Display Load Factor, Drive Frequency and Color Temperature Characteristics

Case	Display Load Factor	Driving Frequency	Power Consumption	Relative composing ratio of each color in white			Embodiment(Correction)		
				Red	Green	Blue	Red	Green	Blue
A	Low	High	Small	Middle	Weaker	Stronger	-	Increased	Decreased
B	High	Low	Large	Middle	Stronger	Weaker	-	Decreased	Increased

FIG. 6




FIG. 7




FIG. 8




FIG. 9





FIG. 10



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

## Declaration and Power of Attorney For Patent Application

### 特許出願宣言書及び委任状

### Japanese Language Declaration

### 日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

PLASMA DISPLAY PANEL WITH CONSTANT

COLOR TEMPERATURE OR COLOR DEVIATION

上記発明の明細書（下記の欄でx印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約国際出願番号を \_\_\_\_\_ とし、  
(該当する場合) \_\_\_\_\_ に訂正されました。

☐ was filed on \_\_\_\_\_  
as United States Application Number or  
PCT International Application Number  
\_\_\_\_\_ and was amended on  
\_\_\_\_\_ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されたとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

## Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

### Prior Foreign Application(s)

外国での先行出願  
11-186818

(Number)  
(番号)

Japan

(Country)  
(国名)

(Number)  
(番号)

(Country)  
(国名)

私は、第35編米国法典119条(e)項に基づいて下記の米国外の特許出願規定に記載された権利をここに主張いたします。

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国外の特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)項に基づく権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国外の特許出願に開示されていない限り、その先行米国外出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じていることに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行えば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed  
優先権主張なし

30/06/1999

(Day/Month/Year Filed)  
(出願年月日)

(Day/Month/Year Filed)  
(出願年月日)

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)  
(出願番号)

(Filing Date)  
(出願日)

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT international application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT international application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of application.

(Status: Patented, Pending, Abandoned)  
(現況: 特許許可済、係属中、放棄済)

(Status: Patented, Pending, Abandoned)  
(現況: 特許許可済、係属中、放棄済)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

### Japanese Language Declaration (日本語宣言書)

委任状: 私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。(弁護士、または代理人の氏名及び登録番号を明記のこと)

James D. Halsey, Jr., 22,729; Harry John Staas, 22,010; David M. Pitcher, 25,908; John C. Garvey, 28,607; J. Randall Beckers, 30,358; William F. Herbert, 31,024; Richard A. Gollhofer, 31,106; Mark J. Henry, 36,162; Gene M. Garner II, 34,172; Michael D. Stein, 37,240; Paul I. Kravetz, 35,230; Gerald P. Joyce, III, 37,648; Todd E. Marlette, 35,269; Harlan B. Williams, Jr., 34,756; George N. Stevens, 36,938; Michael C. Soldner, 41,455; Norman L. Ourada, 41,235; Kevin R. Spivak, P-43,148; and William M. Schertler, 35,348 (agent)

書類送付先

**POWER OF ATTORNEY:** As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

Send Correspondence to:

STAAS & HALSEY  
700 Eleventh Street, N.W.  
Suite 500  
Washington, D.C. 20001

直接電話連絡先: (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

STAAS & HALSEY  
(202) 434-1500

唯一または第一発明者名	Full name of sole or first inventor	Katsuya IRIE
発明者の署名	Inventor's signature	<i>Katsuya Irie</i>
日付	Date	08/06/2000
住所	Residence	Nakahara-ku, Kawasaki-shi, Japan
国籍	Citizenship	Japan
私書箱	Post Office Address	c/o FUJITSU LIMITED, 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki-shi, Kanagawa, 211-8588 Japan
第二共同発明者	Full name of second joint inventor, if any	Fumihiro NAMIKI
第二共同発明者	Second inventor's signature	<i>Fumihiro Namiki</i>
日付	Date	08/06/2000
住所	Residence	Nakahara-ku, Kawasaki-shi, Japan
国籍	Citizenship	Japan
私書箱	Post Office Address	c/o FUJITSU LIMITED, 1-1, Kamikodanaka 4-chome, Nakahara-ku, Kawasaki-shi, Kanagawa, 211-8588 Japan

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)